

DTS-650 & 670

Omni Desktop Scanner

Scan Line : 24 Line

Scan Rate: 2000 Scan per sec.



DTS-650



DTS-670

650nm visible laser diode(VLD)

2000 scans per sec (omnidirectional).

7 angles & 24 line / levels up 4800LUX

Programmable tone & volume

Interface: USB/ RS232

Specification

Spification	DTS-650 and DTS670
Light Source	650nm visible laser diode (VLD)
Depth of field	0-250mm@13mil/0.33mm(PCS=90%)
Scan Pattern	7 directions of scan field
Scan Rate	2,400 scan second (omnidirection)
Numenber of scan Line	7 angles & 24 / Light Levels : Up 4800LUX
Minimum Bar width	5mil @ PCS=90%
Print Contrast	30% @UPC/EAN 100%
Indications(LED)	Two-co;or LED (Standby blue & Read orange)
Beeper operation	Programmable tone & volume
System Interface	Keyboard wedge, RS232, HID USB
Physical	
Dimension	152(L)*152(W)*91(H)mm
Weight	540g(without cable)
Cable	Standard 1.8M straight
Power	
Input Voltage	12VDC±10% , 1.5A
Power Consumption	2.28 watts
Operating Current	190mA
Standy Current	160mA
Regulatory	
Lass Class	CDRH Class IIa; IEC 608525-1: Class
EMC	CE En55022 B , Fcc Part 15 Clasdd B , VCCI , BSMI , Envuronnemental
Environmental	
Operating Temperature	0 Degree~40DegreeC
Storage Temperature	-20 Degree C~60 Degree C (-4 Degree F~140 Degree F)
Linght Level	Up to 4,000 Lux (fluorescence)

OMINI Desktop Scanner
DTS-650 & 660 Scan Barcode : 1D



Specification are subject change without notice